



**YOU GET OUT
WHAT YOU
PUT IN.**



C-915 Fifth Wheel Grease

Kendall® C-915 Fifth Wheel Grease is a smooth-textured calcium grease specially developed to handle the severe loads associated with fifth wheel applications.

C-915 Fifth Wheel Grease is manufactured with a high viscosity base oil, a calcium stearate soap thickener and 10% graphite. It provides high load carrying capacity for protection against wear, and is specially formulated to repel water and resist washout.

Truck Fifth Wheels

Calcium Stearate Grease

10% Graphite

Applications

- Truck fifth wheel plates

Features/Benefits

- High load carrying capacity
- Excellent resistance to water washout



C-915 Fifth Wheel Grease

Typical Properties		
NLGI Grade		1
Thickener Type		Calcium Stearate
Color		Black
Texture		Smooth/Tacky
Density, lbs/gal		8.19
Graphite, wt %		10
Dropping Point, °C (°F)	ASTM D2265	150 (302)
Viscosity, Kinematic	ASTM D445	
Viscosity @ 40°C, cSt		434
Viscosity @ 100°C, cSt		28
Penetration, Worked (60 strokes)	ASTM D217	310-340
Corrosion Prevention	ASTM D1743	Pass
Copper Corrosion	ASTM D4048	1b

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>.

Updated: 12-02-2019

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.