PURITY [™] FG AW HYDRAULIC FLUID 32



00003000529			
Version 3.1		Revision Date 2024/01/17	Print Date 2024/01/17
ECTION 1. IDENTIFICATION			
Product name	:	PURITY ™ FG AW HYDRAULIC FI	LUID 32
Product code	:	PFAW32P20, PFAW32IBC, PFAW	32, PFAW32DRX
Manufacturer or supplier's d		ails Petro-Canada America Lubricants I 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555	-LC
Emergency telephone numb	er		
Emergency telephone number	:	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult loca emergency number(s).	I telephone directory for
Recommended use of the ch	ner	nical and restrictions on use	
Recommended use	:	PURITY FG AW Hydraulic Fluids a fluids and light gear oils.	re food grade hydraulic
		NSF H1 Registered.	
		All components comply with FDA 2 "Lubricants with Incidental Food Co application on industrial and food e added directly to the food product.	ontact". It is intended for
Prepared by	:	Product Safety: +1 905-491-0565	

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Reproductive toxicity	:	Category 2	
GHS label elements Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	Suspected of damaging fertility.	
Precautionary statements	:	Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face	

000003000529

PURITY [™] FG AW HYDRAULIC FLUID 32



0000000020		
Version 3.1	Revision Date 2024/01/17	Print Date 2024/01/17
	protection.	
	Response:	
	IF exposed or concerned: Get me	dical advice/ attention.
	Storage:	
	Store locked up.	
	Disposal:	
	Dispose of contents/ container to plant.	an approved waste disposal
Other hazards None known.		
IARC	No component of this product pres or equal to 0.1% is identified as pr confirmed human carcinogen by I/	obable, possible or
OSHA	No component of this product pres equal to 0.1% is on OSHA's list of	
NTP	No component of this product pres equal to 0.1% is identified as a kno by NTP.	-

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	90 - 100
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	0.1 - 1
2,6-di-tert-butyl-p-cresol	128-37-0	0.1 - 1
Actual concentration is withheld as a ti	rade secret	

SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.

PURITY [™] FG AW HYDRAULIC FLUID 32





Version 3.1		Revision Date 2024/01/17	Print Date 2024/01/17
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention.	r, also under the eyelids,
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless direct physician or poison control center. Never give anything by mouth to an ur Seek medical advice.	
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself. Suspected of damaging fertility.	
Notes to physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), silicon oxides (SiOx), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 3.1

Print Date 2024/01/17

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
2,6-di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TŴA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

:

Respiratory protection

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

PURITY [™] FG AW HYDRAULIC FLUID 32





Version 3.1		Revision Date 2024/01/17	Print Date 2024/01/17
		Respirator selection must be based or exposure levels, the hazards of the pro working limits of the selected respirato	oduct and the safe
Filter type	:	organic vapour filter	
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PV	'A), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves approved standard should be worn at chemical products if a risk assessmen necessary.	all times when handling
Eye protection	:	Wear face-shield and protective suit for problems.	r abnormal processing
Skin and body protection	:	Choose body protection in relation to in concentration and amount of dangerou the specific work-place.	
Protective measures	:	Wash contaminated clothing before re	-use.
Hygiene measures	:	Remove and wash contaminated cloth including the inside, before re-use. Wash face, hands and any exposed sl handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	colourless
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-18 °C (-0.40 °F)
Boiling point/boiling range	:	No data available
Flash point	:	225 °C (437 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Remarks: Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available

PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529



Version 3.1		Revision Date 2024/01/17	Print Date 2024/01/17
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8629 kg/l (59 °F / 15 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	29.8 cSt (104 °F / 40 °C)	
Explosive properties	:	5.2 cSt (212 °F / 100 °C) Do not pressurize, cut, weld, braze, sol expose containers to heat or sources o	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids and alkalis.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, formaldehyde, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

PURITY [™] FG AW HYDRAULIC FLUID 32



000003000529

005000525			
sion 3.1		Revision Date 2024/01/17	Print Date 2024/01/17
Product:			
Acute oral toxicity	:	Remarks: No data available	
Acute inhalation toxicity	:	Assessment: The substance of inhalation toxicity Remarks: No data available	r mixture has no acute
Acute dermal toxicity	:	Remarks: No data available	
Components:			
White mineral oil (petroleur	n):		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
2,6-di-tert-butyl-p-cresol: Acute oral toxicity	:	LD50 (Rat): 6,000 mg/kg,	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation Not classified due to lack of d Product:	lata.		
Product:		No. 1979 - Plante	
Remarks	:	No data available	
Serious eye damage/eye irr			
Not classified due to lack of d	ala.		
Product: Remarks	:	No data available	
Respiratory or skin sensitis	satic	n	
Skin sensitisation			
Not classified due to lack of d	lata.		
Respiratory sensitisation			
Not classified due to lack of d	lata.		
Germ cell mutagenicity Not classified due to lack of d	lata.		
Carcinogenicity			
Not classified due to lack of d	lata.		
Reproductive toxicity			
Suspected of damaging fertili	ty.		
STOT - single exposure Not classified due to lack of d	lata.		
ot www.potrocondel.html.		ada	
net: www.petrocanadalubricants.c	Join/	505	Page: 7 / Patro Canada Lubricants is a HE Sinclair b

PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 3.1

Revision Date 2024/01/17

Print Date 2024/01/17

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:					
Toxicity to fish	:	Remarks: No data available			
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available			
Toxicity to algae/aquatic plants	:	Remarks: No data available			
Toxicity to microorganisms	:	Remarks: No data available			
Persistence and degradability					
Product:					
Biodegradability	:	Remarks: No data available			
Bioaccumulative potential					
No data available					
Mobility in soil					
No data available					
Other adverse effects					
No data available					
CTION 13 DISPOSAL CONSIL	שבר				

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal
	of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 3.1

Revision Date 2024/01/17

Print Date 2024/01/17

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. For more information go to www.P65Warnings.ca.gov.
The components of this proc	duc	t are reported in the following inventories:
DSL	:	On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory
	:	HSNO: HSR002605, Lubricants (Low Hazard) Group Standard 2020

SECTION 16. OTHER INFORMATION


Further information

PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 3.1

Revision Date 2024/01/17



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*' represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA		8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 3.1

Revision Date 2024/01/17

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: www.petrocanadalubricants.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2024/01/17 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2024/01/17