

Universal Oil Full Synthetic HD 5W40 CK-4 Revision Date: 02-20-2019

1. Identification	
Product identifier used on the label: Oil Product Code:	Universal Oil Full Synthetic HD 5W40 CK-4 Motor 663
Other means of identification: Synonyms:	No data available
Recommended use of the chemical and r Recommended use:	estrictions on use: Motor Oil
Restrictions on use:	Uses other than those described above
Name, address, and telephone number	Universal Oil
of the chemical manufacturer, importer, or other responsible party:	265 Jefferson Ave.
importer, or other responsible party.	Cleveland, OH 44113
Phone number:	+01 (216) 771 - 4300
Emergency phone number:	CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887
2. Hazard(s) identification	

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification:	Not classified as hazardous under OSHA
Hazards not otherwise classified:	No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Petroleum distillates, solvent dewaxed heavy paraffinic	No data available	64742-65-0	3 - 7
Phenol, (tetrapropenyl) derivitives	No data available	74499-35-7	0.1 - 1

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
Most important symptoms/effects, acute and delayed:	
Indication of immediate medical attention and special treatment needed, if necessary:	No additional first aid information available.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	No data available
Hazardous combustion products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide, Smoke
Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

6. Accidental release measures		

Personal precautions, protective

Exposure to the spilled material may be irritating or harmful. Follow

Universal Oil Full Synthetic HD 5W40 CK-4 Revision Date: 02-20-2019

equipment and emergency procedures:	personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods and materials for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.
7. Handling and storage	
Precautions for safe handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer. Follow all protective equipment recommendations provided in Section 8.
Conditions for safe storage, including any incompatibilities: Safe storage conditions:	Store in a cool dry place. Isolate from incompatible materials.
Materials to Avoid/Chemical Incompatibility:	Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Lubricating oils	5 mg/m3	5 mg/m3	10 mg/m3	No data available
(petroleum), C20-50,				
hydrotreated neutral oil-				
based				
Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available
hydrotreated heavy				
paraffinic				
Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

	
solvent dewaxed heavy paraffinic	
Appropriate engineering controls:	Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.
Individual protection measures, such	as personal protective equipment:
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
Eye protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.
Skin protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves:	Nitrile, Neoprene
General hygiene conditions:	Follow all protective equipment recommendations provided in Section 8.

9. Physical and chemical properties

Appearance (physical state, color etc.):	
Physical state:	Liquid
Color:	Brown
Odor:	Mild
Odor Threshold:	Not determined
pH:	No data available
Melting point/freezing point:	
Melting Point:	No data available
Freezing point:	No data available
Initial boiling point and boiling range (°C):	COC
Flash Point (°C):	226

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability or explosive limits:	
Upper flammability or explosive limits:	= 10
Lower flammability or explosive limits:	= 1
Vapor pressure:	No data available
Vapor density:	No data available
Relative density:	0.85
Solubility(ies):	Negligible
Partition coefficient: n-octanol/water:	3.9
Auto-ignition temperature:	No data available
Decomposition Temperature:	Not determined
Viscosity cSt @ 40°C:	81.3

10. Stability and reactivity

Reactivity:	There are no known reactivity hazards associated with this product.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide, Smoke

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:					
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact, Inhalation, Ingestion, Eye contact				
Symptoms related to the physical,	No data available				

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

chemical and toxicological characteristics:	
Delayed and immediate effects and also	chronic effects from short- and long-term exposure:
Ingestion:	No hazard in normal industrial use. Estimated to be > 5.0 g/kg.
Skin Contact:	This material is likely to be moderately irritating to skin based on animal data.Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Absorption:	Estimated to be > 5.0 g/kg; practically non-toxic
Inhalation:	No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.
Eye Contact:	The material is likely to be moderately irritating to eyes based on animal data. Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Sensitization:	Non-hazardous under Respiratory Sensitization category.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, solvent dewaxed heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat = 2.18 mg/L

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Severe ecological hazard. This product may be toxic to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	72623-87-1	Aquatic EC50 (48h) Daphnia > 1000 mg/L	No data available	Aquatic LC50 (96h) > 5000 mg/L

Persistence and degradability:	Biodegrades slowly.
Persistence and degradability:	Biodegrades slowly.

Bioaccumulative potential:Bioconcentration may occur.Mobility in soil:This material is expected to have essentially no mobility in soil. It absorbs
strongly to most soil types.

None known.

Other adverse effects (such as hazardous to the ozone layer):

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging: Spent or discarded material is non-hazardous according to environmental regulations.

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

Contaminated packaging: Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:			
DOT Basic Description:	No data available		
International carriage of dangerous good	ls by sea (IMDG/IMO):		
UN number:	Not regulated by IMDG		
UN Proper shipping name:	Not applicable		
Transport hazard class(es):	Not applicable		
Packing group, if applicable:	Not applicable		
International carriage of dangerous good	ls by air (IATA):		
UN number:	Not regulated by IATA		
UN Proper shipping name:	Not applicable		
Transport hazard class(es):	Not applicable		
Packing group, if applicable:	Not applicable		
Environmental hazards (e.g., Marine	None.		
pollutant (Yes/No)):			
Transport in bulk (according to Annex II	No data available		
of MARPOL 73/78 and the IBC Code):			
Special precautions which a user needs	No data available		
to be aware of or needs to comply with			
in connection with transport or conveyance either within or outside			
their premises:			
•			

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status:

All components of this material are on the US TSCA Inventory or are exempt.

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Lubricating oils					
(petroleum), C20-50,	72623-87-1	Ν	N	N	N
hydrotreated neutral	/2023-0/-1	IN	IN		IN
oil-based					
Petroleum distillates,					
hydrotreated heavy	64742-54-7	Ν	Ν	N	N
paraffinic					
Petroleum distillates,					
solvent dewaxed	64742-65-0	Ν	Ν	N	N
heavy paraffinic					
Phenol,					
(tetrapropenyl)	74499-35-7	Ν	Ν	N	N
derivitives					

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	Ν	Ν	Ν	Ν
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Ν	Ν	Ν	Ν
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Ν	Ν	Ν	Ν
Phenol, (tetrapropenyl) derivitives	74499-35-7	Ν	Ν	Ν	Ν

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-87-1	Ν	Ν	Ν	Ν	Ν

Universal Oil Full Synthetic HD 5W40 CK-4

Revision Date: 02-20-2019

oil-based						
Petroleum distillates,						
hydrotreated heavy	64742-54-7	Ν	N	N	N	N
paraffinic						
Petroleum distillates,						
solvent dewaxed	64742-65-0	Ν	N	N	N	N
heavy paraffinic						
Phenol,						
(tetrapropenyl)	74499-35-7	Ν	N	N	N	Ν
derivitives						

16. Other information, including date of preparation or last revision.

Revision Date: Revision Number:

Reason for revision: References: Other Info:

Disclaimer:

02-20-2019 42 NEW VERSION No data available

No data available

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.